

Unit Testing Framework

Thomas Braun © 2013
www.byte-physics.de

Version 1.0 compiled on Wed Feb 27 2013 11:59:34

Contents

1	Main Page	1
1.1	Assertion Types	1
1.2	Test Case	1
1.3	Test Suite	1
1.4	Test Hooks	1
1.5	Automate Test Runs	2
2	Module Documentation	2
2.1	Helper functions	2
2.2	Test Assertions	4
2.3	Assertions flags	9
2.4	Wave existence flags	10
2.5	Wave equality flags	11
2.6	Default hook functions	12
3	Example Documentation	14
3.1	example1-plain.ipf	14
3.2	example2-plain.ipf	14
3.3	example3-plain.ipf	15
3.4	example4-wavechecking.ipf	15
3.5	example5-overridehooks.ipf	15
3.6	Example6/example6-automatic-invocation.ipf	16

1 Main Page

This package empowers a programmer to utilize unit testing for Igor Pro procedures and XOPs. For a quick start have a look at the [first example](#).

The basic building blocks of this package are [Assertions](#) (for checking if an entity fulfills specific properties), [Test Cases](#) (group of assertions) and [Test Suites](#) (group of test cases).

Interface design and naming is inspired by the [Boost Test Library](#).

1.1 Assertion Types

An assertion checks that a given condition is true. Or in more general terms that an entity fulfills specific properties. Test assertions are defined for strings, variables and waves and have ALL CAPS names. They always come in triplets which differ only in how they react on a failed assertion. Comparing two variables for example can be done with [WARN_EQUAL_VAR](#), [CHECK_EQUAL_VAR](#) or [REQUIRE_EQUAL_VAR](#).

The following table summarizes the action on a failed assertion:

Type	Create Log Message	Increment Error Count	Abort execution immediately
WARN	YES	NO	NO
CHECK	YES	YES	NO
REQUIRE	YES	YES	YES

If in doubt use the CHECK variant. For the sake of clarity only the CHECK variants are documented, as the interface for REQUIRE and WARN is equivalent.

1.2 Test Case

A test case is one of the basic building blocks grouping assertions together. A function is considered a test case if it fulfills all of the following properties:

- takes no parameters
- its name does not end on `_IGNORE`
- is either non-static or static and part of a regular module

The second rule allows advanced users to add their own helper functions. It is advised to define all test cases as static functions and to create one regular module per procedure file.

A single test case from a test suite can be run using the optional `testCase` parameter of [RunTest](#).

1.3 Test Suite

A test suite is a group of test cases which should belong together and is equal to a procedure file. Therefore tests suites can not be nested, although multiple test suites can be run with once command using the parameter `procWinList` of [RunTest](#).

1.4 Test Hooks

To ensure proper test case execution and enable book keeping, specific hook functions are called before/after distinct events. These hook functions always come in pairs with their names ending on `_BEGIN` and `_END`. Before the first test case of the first test suite is executed, the hook [TEST_BEGIN](#) is called, therefore [TEST_END](#) marks

the last function being called immediately before `RunTest` returns. Similarly the hooks `TEST_SUITE_BEGIN` and `TEST_SUITE_END` are called before and after every test suite, `TEST_CASE_BEGIN` and `TEST_CASE_END` before and after every test case.

In case the default hook functions don't suite your needs, it is explicitly **not** advised to just adapt them. Instead use [test hook overrides](#) and override them on a global or per test suite level.

1.4.1 Override Test Hooks

The default test hooks can be overridden by defining your own version of the hooks suffixed with `_OVERRIDE`. The override hooks for `TEST_BEGIN` and `TEST_END` can only be overridden by functions in ProcGlobal. The override hooks for test suites/cases can be overridden globally if they reside in ProcGlobal context, or for a specific test suite only if they are defined in the same regular module as that test suite. Overriding here means that the default test hook is **not** executed. In case you still want to have the default test hook executed, you have to call it yourself in the override function as done in [example 5](#).

The override test hooks have to accept exactly one string parameter, which is the name of the test suite group, test suite name or test case name.

1.5 Automate Test Runs

To further simplify test execution it is possible to automate test runs from the command line.

Steps to do that include:

- Implement a function called `run` in ProcGlobal context taking no parameters. This function must perform all necessary steps for test execution, which is at least one call to [RunTest](#).
- Put the test experiment together with your test suites (procedure files) and the script helper/autorun-test.bat into its own folder
- Run the batch file autorun-test.bat
- Inspect the created log file

See also [Example6/example6-automatic-invocation.ipf](#)

2 Module Documentation

2.1 Helper functions

Functions

- variable [DisableDebugOutput](#) ()
- variable [EnableDebugOutput](#) ()
- variable [RunTest](#) (string procWinList, string name, string testCase)

2.1.1 Detailed Description

Runner and helper functions.

2.1.2 Function Documentation

variable [DisableDebugOutput](#) ()

Turns debug output off.

variable EnableDebugOutput ()

Turns debug output on.

variable RunTest (string *procWinList*, string *name*, string *testCase*)

Main function to execute one or more test suites.

Parameters

<i>procWinList</i>	semicolon (";") separated list of procedure files
<i>name</i>	(optional) descriptive name for the executed test suites
<i>testCase</i>	(optional) function name, resembling one test case, which should be executed only

Returns

total number of errors

Examples:

[example2-plain.ipf](#), and [Example6/example6-automatic-invocation.ipf](#).

2.2 Test Assertions

Functions

- variable `CHECK` (variable *var*)
- variable `CHECK_CLOSE_VAR` (variable *var1*, variable *var2*, variable *tol*, variable *strong_or_weak*)
- variable `CHECK_EMPTY_FOLDER` ()
- variable `CHECK_EMPTY_STR` (string **str*)
- variable `CHECK_EQUAL_STR` (string **str1*, string **str2*, variable *case_sensitive*)
- variable `CHECK_EQUAL_VAR` (variable *var1*, variable *var2*)
- variable `CHECK_EQUAL_WAVES` (Wave/Z *wv1*, Wave/Z *wv2*, variable *mode*, variable *tol*)
- variable `CHECK_NEQ_STR` (string **str1*, string **str2*, variable *case_sensitive*)
- variable `CHECK_NEQ_VAR` (variable *var1*, variable *var2*)
- variable `CHECK_NULL_STR` (string **str*)
- variable `CHECK_SMALL_VAR` (variable *var*, variable *tol*)
- variable `CHECK_WAVE` (Wave/Z *wv*, variable *majorType*, variable *minorType*)
- variable `FAIL` ()
- variable `REQUIRE` (variable *var*)
- variable `REQUIRE_CLOSE_VAR` (variable *var1*, variable *var2*, variable *tol*, variable *strong_or_weak*)
- variable `REQUIRE_EMPTY_FOLDER` ()
- variable `REQUIRE_EMPTY_STR` (string **str*)
- variable `REQUIRE_EQUAL_STR` (string **str1*, string **str2*, variable *case_sensitive*)
- variable `REQUIRE_EQUAL_VAR` (variable *var1*, variable *var2*)
- variable `REQUIRE_EQUAL_WAVES` (Wave/Z *wv1*, Wave/Z *wv2*, variable *mode*, variable *tol*)
- variable `REQUIRE_NEQ_STR` (string **str1*, string **str2*, variable *case_sensitive*)
- variable `REQUIRE_NEQ_VAR` (variable *var1*, variable *var2*)
- variable `REQUIRE_NULL_STR` (string **str*)
- variable `REQUIRE_SMALL_VAR` (variable *var*, variable *tol*)
- variable `REQUIRE_WAVE` (Wave/Z *wv*, variable *majorType*, variable *minorType*)
- variable `WARN` (variable *var*)
- variable `WARN_CLOSE_VAR` (variable *var1*, variable *var2*, variable *tol*, variable *strong_or_weak*)
- variable `WARN_EMPTY_FOLDER` ()
- variable `WARN_EMPTY_STR` (string **str*)
- variable `WARN_EQUAL_STR` (string **str1*, string **str2*, variable *case_sensitive*)
- variable `WARN_EQUAL_VAR` (variable *var1*, variable *var2*)
- variable `WARN_EQUAL_WAVES` (Wave/Z *wv1*, Wave/Z *wv2*, variable *mode*, variable *tol*)
- variable `WARN_NEQ_STR` (string **str1*, string **str2*, variable *case_sensitive*)
- variable `WARN_NEQ_VAR` (variable *var1*, variable *var2*)
- variable `WARN_NULL_STR` (string **str*)
- variable `WARN_SMALL_VAR` (variable *var*, variable *tol*)
- variable `WARN_WAVE` (Wave/Z *wv*, variable *majorType*, variable *minorType*)

2.2.1 Detailed Description

Test assertions for variables, strings, waves and helper functions.

2.2.2 Function Documentation

variable `CHECK` (variable *var*)

Tests if *var* is true (1).

Parameters

<i>var</i>	variable to test
------------	------------------

variable CHECK_CLOSE_VAR (variable *var1*, variable *var2*, variable *tol*, variable *strong_or_weak*)

Compares two variables and determines if they are close.

Based on the implementation of "Floating-point comparison algorithms" in the C++ Boost unit testing framework.

Literature:

The art of computer programming (Vol II). Donald. E. Knuth. 0-201-89684-2. Addison-Wesley Professional; 3 edition, page 234 equation (34) and (35).

Parameters

<i>var1</i>	first variable
<i>var2</i>	second variable
<i>tol</i>	(optional) tolerance, defaults to 1e-8
<i>strong_or_weak</i>	(optional) type of condition, can be 0 for weak or 1 for strong (default)

Examples:

[example5-overridehooks.ipf](#).

variable CHECK_EMPTY_FOLDER ()

Tests if the current data folder is empty.

Counted are objects with type waves, strings, variables and folders

Examples:

[example4-wavechecking.ipf](#).

variable CHECK_EMPTY_STR (string * *str*)

Tests if *str* is empty.

A null string is never empty.

Parameters

<i>str</i>	string to test
------------	----------------

Examples:

[example2-plain.ipf](#).

variable CHECK_EQUAL_STR (string * *str1*, string * *str2*, variable *case_sensitive*)

Compares two strings for equality.

Parameters

<i>str1</i>	first string
<i>str2</i>	second string
<i>case_sensitive</i>	(optional) should the comparison be done case sensitive (1) or case insensitive (0, the default)

Examples:

[example2-plain.ipf](#).

variable CHECK_EQUAL_VAR (variable *var1*, variable *var2*)

Tests two variables for equality.

For variables holding floating point values it is often more desirable use CHECK_CLOSE_VAR instead. To fulfill semantic correctness this assertion treats two variables with both holding NaN as equal.

Parameters

<i>var1</i>	first variable
<i>var2</i>	second variable

Examples:

[example1-plain.ipf](#), [example2-plain.ipf](#), [example3-plain.ipf](#), [example4-wavechecking.ipf](#), [example5-overridehooks.ipf](#), and [Example6/example6-automatic-invocation.ipf](#).

variable CHECK_EQUAL_WAVES (Wave/Z *wv1*, Wave/Z *wv2*, variable *mode*, variable *tol*)

Tests two waves for equality.

Parameters

<i>wv1</i>	first wave
<i>wv2</i>	second wave
<i>mode</i>	(optional) features of the waves to compare, defaults to all modes, defined at Wave equality flags
<i>tol</i>	(optional) tolerance for comparison, by default 0.0 which does byte-by-byte comparison (relevant only for mode=WAVE_DATA)

Examples:

[example4-wavechecking.ipf](#).

variable CHECK_NEQ_STR (string * *str1*, string * *str2*, variable *case_sensitive*)

Compares two strings for unequality.

Parameters

<i>str1</i>	first string
<i>str2</i>	second string
<i>case_sensitive</i>	(optional) should the comparison be done case sensitive (1) or case insensitive (0, the default)

Examples:

[example2-plain.ipf](#).

variable CHECK_NEQ_VAR (variable *var1*, variable *var2*)

Tests two variables for inequality.

Parameters

<i>var1</i>	first variable
<i>var2</i>	second variable

variable CHECK_NULL_STR (string * *str*)

Tests if str is null.

An empty string is never null.

Parameters

<i>str</i>	string to test
------------	----------------

Examples:

[example2-plain.ipf](#).

variable CHECK_SMALL_VAR (variable *var*, variable *tol*)

Tests if a variable is small using the inequality $|var| < |tol|$.

Parameters

<i>var</i>	variable
<i>tol</i>	(optional) tolerance, defaults to 1e-8

variable CHECK_WAVE (Wave/Z *wv*, variable *majorType*, variable *minorType*)

Tests a wave for existence and its type.

Parameters

<i>wv</i>	wave reference
<i>majorType</i>	major wave type
<i>minorType</i>	(optional) minor wave type

See also

[Wave existence flags](#)

Examples:

[example4-wavechecking.ipf](#).

variable FAIL ()

Force the test case to fail.

variable REQUIRE (variable *var*)

variable REQUIRE_CLOSE_VAR (variable *var1*, variable *var2*, variable *tol*, variable *strong_or_weak*)

variable REQUIRE_EMPTY_FOLDER ()

variable REQUIRE_EMPTY_STR (string * *str*)

variable REQUIRE_EQUAL_STR (string * *str1*, string * *str2*, variable *case_sensitive*)

variable REQUIRE_EQUAL_VAR (variable *var1*, variable *var2*)

Examples:

[example3-plain.ipf](#).

variable REQUIRE_EQUAL_WAVES (Wave/Z *wv1*, Wave/Z *wv2*, variable *mode*, variable *tol*)

variable REQUIRE_NEQ_STR (string * *str1*, string * *str2*, variable *case_sensitive*)

variable REQUIRE_NEQ_VAR (variable *var1*, variable *var2*)

variable REQUIRE_NULL_STR (string * *str*)

variable REQUIRE_SMALL_VAR (variable *var*, variable *tol*)

variable REQUIRE_WAVE (Wave/Z *wv*, variable *majorType*, variable *minorType*)

variable WARN (variable *var*)

Examples:

[example1-plain.ipf](#).

variable WARN_CLOSE_VAR (variable *var1*, variable *var2*, variable *tol*, variable *strong_or_weak*)

variable WARN_EMPTY_FOLDER ()

variable WARN_EMPTY_STR (string * *str*)

variable WARN_EQUAL_STR (string * *str1*, string * *str2*, variable *case_sensitive*)

Examples:

[example2-plain.ipf](#).

variable WARN_EQUAL_VAR (variable *var1*, variable *var2*)

Examples:

[example3-plain.ipf](#).

variable WARN_EQUAL_WAVES (Wave/Z *wv1*, Wave/Z *wv2*, variable *mode*, variable *tol*)

variable WARN_NEQ_STR (string * *str1*, string * *str2*, variable *case_sensitive*)

variable WARN_NEQ_VAR (variable *var1*, variable *var2*)

variable WARN_NULL_STR (string * *str*)

variable WARN_SMALL_VAR (variable *var*, variable *tol*)

variable WARN_WAVE (Wave/Z *wv*, variable *majorType*, variable *minorType*)

2.3 Assertions flags

Modules

- [Wave existence flags](#)
- [Wave equality flags](#)

2.3.1 Detailed Description

Constants for assertion test tuning.

2.4 Wave existence flags

Variables

- const variable `COMPLEX_WAVE` = 0x01
- const variable `DOUBLE_WAVE` = 0x04
- const variable `FLOAT_WAVE` = 0x02
- const variable `INT16_WAVE` = 0x16
- const variable `INT32_WAVE` = 0x20
- const variable `INT8_WAVE` = 0x08
- const variable `NUMERIC_WAVE` = 1
- const variable `TEXT_WAVE` = 2
- const variable `UNSIGNED_WAVE` = 0x40

2.4.1 Detailed Description

Values for `majorType` / `minorType` of `WARN_WAVE`, `CHECK_WAVE` and `REQUIRE_WAVE`.

2.4.2 Variable Documentation

const variable `COMPLEX_WAVE` = 0x01

const variable `DOUBLE_WAVE` = 0x04

Examples:

[example4-wavechecking.ipf](#).

const variable `FLOAT_WAVE` = 0x02

const variable `INT16_WAVE` = 0x16

const variable `INT32_WAVE` = 0x20

const variable `INT8_WAVE` = 0x08

const variable `NUMERIC_WAVE` = 1

Examples:

[example4-wavechecking.ipf](#).

const variable `TEXT_WAVE` = 2

Examples:

[example4-wavechecking.ipf](#).

const variable `UNSIGNED_WAVE` = 0x40

2.5 Wave equality flags

Variables

- const variable `DATA_FULL_SCALE` = 256
- const variable `DATA_UNITS` = 8
- const variable `DIMENSION_LABELS` = 32
- const variable `DIMENSION_SIZES` = 512
- const variable `DIMENSION_UNITS` = 16
- const variable `WAVE_DATA` = 1
- const variable `WAVE_DATA_TYPE` = 2
- const variable `WAVE_LOCK_STATE` = 128
- const variable `WAVE_NOTE` = 64
- const variable `WAVE_SCALING` = 4

2.5.1 Detailed Description

Values for `mode` in `WARN_EQUAL_WAVES`, `CHECK_EQUAL_WAVES` and `REQUIRE_EQUAL_WAVES`.

2.5.2 Variable Documentation

const variable `DATA_FULL_SCALE` = 256

const variable `DATA_UNITS` = 8

const variable `DIMENSION_LABELS` = 32

const variable `DIMENSION_SIZES` = 512

const variable `DIMENSION_UNITS` = 16

const variable `WAVE_DATA` = 1

const variable `WAVE_DATA_TYPE` = 2

const variable `WAVE_LOCK_STATE` = 128

const variable `WAVE_NOTE` = 64

const variable `WAVE_SCALING` = 4

2.6 Default hook functions

Functions

- variable `TEST_BEGIN` (string name)
- variable `TEST_CASE_BEGIN` (string testCase)
- variable `TEST_CASE_END` (string testCase)
- variable `TEST_END` (string name)
- variable `TEST_SUITE_BEGIN` (string testSuite)
- variable `TEST_SUITE_END` (string testSuite)

2.6.1 Detailed Description

Default implementation of test hook functions.

2.6.2 Function Documentation

variable `TEST_BEGIN` (string *name*)

Default test begin hook.

The hook is immediately called after RunTest starts.

Parameters

<i>name</i>	name of the test suite group
-------------	------------------------------

variable `TEST_CASE_BEGIN` (string *testCase*)

Default hook for test case begin.

The hook is called before executing the test case.

Parameters

<i>testCase</i>	name of the test case
-----------------	-----------------------

variable `TEST_CASE_END` (string *testCase*)

Default hook for test case end.

The hook is called after executing the test case.

Parameters

<i>testCase</i>	name of the test case
-----------------	-----------------------

Examples:

[example5-overridehooks.ipf](#).

variable `TEST_END` (string *name*)

Default test end hook.

The hook is called after all tests suites.

Parameters

<i>name</i>	name of the test suite group
-------------	------------------------------

variable `TEST_SUITE_BEGIN (string testSuite)`

Default hook for test suite begin.

The hook is called before executing the first test case of every test suite.

Parameters

<i>testSuite</i>	name of the test suite
------------------	------------------------

variable `TEST_SUITE_END (string testSuite)`

Default hook for test suite end.

The hook is called after executing the last test case of every test suite.

Parameters

<i>testSuite</i>	name of the test suite
------------------	------------------------

Examples:

[example5-overridehooks.ipf](#).

3 Example Documentation

3.1 example1-plain.ipf

Test suite showing the basic working principles.

```
#pragma rtGlobals=3

#include "unit-testing"

// Execute the test suite, same named as this procedure file
// with RunTest("example1-plain.ipf")

Function TestModulo()

    CHECK_EQUAL_VAR(abs(1.5),1.5)
    CHECK_EQUAL_VAR(abs(-1.5),1.5)
    CHECK_EQUAL_VAR(abs(NaN),NaN)
    // remember that NaN is not equal to NaN
    // this check will generate a warning message but due
    // to the usage of WARN instead of CHECK not increment the error count
    WARN(abs(NaN) == NaN)
    CHECK_EQUAL_VAR(abs(INF),INF)
    CHECK_EQUAL_VAR(abs(-INF),INF)
End
```

3.2 example2-plain.ipf

Test suite with run routine and module/static usage. See the section about [test cases](#) why the function run_IGNORE() is not considered a test case.

```
#pragma rtGlobals=3
#pragma ModuleName=Example2

#include "unit-testing"

// Command: run_IGNORE()
// Shows how to use ignore routines

Function run_IGNORE()
    // All of these commands run the test suite "example2-plain.ipf"

    // executes all test cases of this file
    RunTest("example2-plain.ipf")
    // execute only one test case at a time
    RunTest("example2-plain.ipf",testCase="VerifyDefaultStringBehaviour")
    // Give all test suites a descriptive name
    RunTest("example2-plain.ipf",name="My first test")
End

// Making the function static prevents name clashes with other procedure files.
// Using static functions requires also the line "#pragma ModuleName" from
// above.
static Function VerifyDefaultStringBehaviour()

    string nullString
    string emptyString = ""
    string strLow      = "1234a"
    string strUP       = "1234A"

    // by default string comparison is done case insensitive
    CHECK_EQUAL_STR(strLow,strUP)
    CHECK_EQUAL_STR(strLow,strUP,case_sensitive=0)
    // the next test fails
    WARN_EQUAL_STR(strLow,strUP,case_sensitive=1)

    CHECK_NEQ_STR(emptyString,nullString)
    CHECK_NEQ_STR(strLow,nullString)
    CHECK_EMPTY_STR(emptyString)
    CHECK_NULL_STR(nullString)
    CHECK_EQUAL_VAR(strlen(strLow),5)
End
```


3.3 example3-plain.ipf

Test suite emphasising the difference between the WARN, CHECK and REQUIRE assertion variants. See also [Assertion Types](#).

```
#pragma rtGlobals=3
#pragma ModuleName=Example3

#include "unit-testing"

// Command: RunTest("example3-plain.ipf")
// The error count of this test suite is 2

// WARN_* does not increment the error count
Function WarnTest()

    WARN_EQUAL_VAR(1.0,0.0)
End

// CHECK_* increments the error count
Function CheckTest()

    CHECK_EQUAL_VAR(1.0,0.0)
End

// REQUIRE_* increments the error count and will stop execution
// of the test case immediately.
// Nevertheless the test end hooks are still executed.
Function RequireTest()

    REQUIRE_EQUAL_VAR(1.0,0.0)
    print "I'm never reached :("
End
```

3.4 example4-wavechecking.ipf

Test suite showing some test assertions for waves.

```
#pragma rtGlobals=3
#pragma ModuleName=Example4

#include "unit-testing"

// Command: RunTest("example4-wavechecking.ipf")
// Helper functions to check wave types and compare with
// reference waves are also provided

static Function CheckMakeDouble()
    CHECK_EMPTY_FOLDER() // checks that the cdf is completely
        empty

    Make/D myWave
    CHECK_WAVE(myWave, NUMERIC_WAVE, minorType=DOUBLE_WAVE
    )
    CHECK_EQUAL_VAR(DimSize(myWave,0),128)

    // as this test case is always executed in a fresh datafolder
    // we don't have to use the overwrite /O option for Duplicate
    Duplicate myWave, myWaveCopy
    CHECK_EQUAL_WAVES(myWave, myWaveCopy)
End

static Function CheckMakeText()
    CHECK_EMPTY_FOLDER()

    Make/T/D myWave
    CHECK_WAVE(myWave, TEXT_WAVE)
    CHECK_EQUAL_VAR(DimSize(myWave,0),128)

    Duplicate myWave, myWaveCopy
    CHECK_EQUAL_WAVES(myWave, myWaveCopy)
End
```

3.5 example5-overridehooks.ipf

Two test suites showing how to use test hook overrides.

```

#pragma rtGlobals=3

#include "unit-testing"

// As this procedure file is in ProcGlobal context
// the test hook overrides are global.

Function TEST_BEGIN_OVERRIDE(name)
    string name

    print "I can only be overridden globally"
End

Function TEST_END_OVERRIDE(name)
    string name

    print "I can only be overridden globally, too"
End

Function TEST_CASE_END_OVERRIDE(name)
    string name

    print "I'm for all test suites overriding the test case end but still call
        the default hook"
    TEST_CASE_END(name)
End

Function TEST_SUITE_BEGIN_OVERRIDE(name)
    string name

    print "Global test suite begin override"
End

Function TEST_SUITE_END_OVERRIDE(name)
    string name

    print "Global test suite end override"
    TEST_SUITE_END(name)
End

Function CheckBasicMath()

    CHECK_EQUAL_VAR(1+2,3)
End

#pragma rtGlobals=3
#pragma ModuleName=Example5

#include "unit-testing"

// RunTest("example5-overridehooks.ipf;example5-overridehooks-otherSuite.ipf")

static Function TEST_CASE_BEGIN_OVERRIDE(name)
    string name

    print "I'm for all test cases in this test suite overriding the test case
        begin"
End

static Function TEST_CASE_END_OVERRIDE(name)
    string name

    printf "I'm overriding test case end for (%s) in this test suite only but
        still call the default hook\r", name
    TEST_CASE_END(name)
End

static Function CheckSquareRoot()

    CHECK_EQUAL_VAR(sqrt(4.0),2.0)
    CHECK_CLOSE_VAR(sqrt(2.0),1.4142,tol=1e-4)
End

```

3.6 Example6/example6-automatic-invocation.ipf

Test suite showing how to automate testing from the command line. See also [Automate Test Runs](#).

```

#pragma rtGlobals=3

#include "unit-testing"

```

```
Function run()  
    RunTest("example6-automatic-invocation.ipf")  
End  
  
#pragma rtGlobals=3  
#pragma ModuleName=Example6  
  
#include "unit-testing"  
  
// Command: Call "autorun-test.bat" without Igor Pro running  
  
static Function CheckTrigonometricFunctions()  
    CHECK_EQUAL_VAR(sin(0.0), 0.0)  
    CHECK_EQUAL_VAR(cos(0.0), 1.0)  
    CHECK_EQUAL_VAR(tan(0.0), 0.0)  
End
```

A		Helper functions 2	
Assertions flags 9			
C		F	
CHECK		FAIL	
Test Assertions 4		Test Assertions 7	
CHECK_CLOSE_VAR		FLOAT_WAVE	
Test Assertions 5		Wave existence flags 10	
CHECK_EMPTY_FOLDER		H	
Test Assertions 5		Helper functions 2	
CHECK_EMPTY_STR		DisableDebugOutput 2	
Test Assertions 5		EnableDebugOutput 2	
CHECK_EQUAL_STR		RunTest 3	
Test Assertions 5		I	
CHECK_EQUAL_VAR		INT16_WAVE	
Test Assertions 5		Wave existence flags 10	
CHECK_EQUAL_WAVES		INT32_WAVE	
Test Assertions 6		Wave existence flags 10	
CHECK_NEQ_STR		INT8_WAVE	
Test Assertions 6		Wave existence flags 10	
CHECK_NEQ_VAR		N	
Test Assertions 6		NUMERIC_WAVE	
CHECK_NULL_STR		Wave existence flags 10	
Test Assertions 6		R	
CHECK_SMALL_VAR		REQUIRE	
Test Assertions 7		Test Assertions 7	
CHECK_WAVE		REQUIRE_CLOSE_VAR	
Test Assertions 7		Test Assertions 7	
COMPLEX_WAVE		REQUIRE_EMPTY_FOLDER	
Wave existence flags 10		Test Assertions 7	
D		REQUIRE_EMPTY_STR	
DATA_FULL_SCALE		Test Assertions 7	
Wave equality flags 11		REQUIRE_EQUAL_STR	
DATA_UNITS		Test Assertions 7	
Wave equality flags 11		REQUIRE_EQUAL_VAR	
DIMENSION_LABELS		Test Assertions 7	
Wave equality flags 11		REQUIRE_EQUAL_WAVES	
DIMENSION_SIZES		Test Assertions 7	
Wave equality flags 11		REQUIRE_NEQ_STR	
DIMENSION_UNITS		Test Assertions 7	
Wave equality flags 11		REQUIRE_NEQ_VAR	
DOUBLE_WAVE		Test Assertions 7	
Wave existence flags 10		REQUIRE_NULL_STR	
Default hook functions 12		Test Assertions 8	
TEST_BEGIN 12		REQUIRE_SMALL_VAR	
TEST_CASE_BEGIN 12		Test Assertions 8	
TEST_CASE_END 12		REQUIRE_WAVE	
TEST_END 12		Test Assertions 8	
TEST_SUITE_BEGIN 13		RunTest	
TEST_SUITE_END 13		Helper functions 3	
DisableDebugOutput		T	
Helper functions 2		TEST_BEGIN	
E		Default hook functions 1	
EnableDebugOutput			

TEST_CASE_BEGIN	Test Assertions	8
Default hook functions		12
TEST_CASE_END	Test Assertions	8
Default hook functions		12
TEST_END	Test Assertions	8
Default hook functions		12
TEST_SUITE_BEGIN	Test Assertions	8
Default hook functions		13
TEST_SUITE_END	Test Assertions	8
Default hook functions		13
TEXT_WAVE	Test Assertions	8
Wave existence flags		10
Test Assertions		4
CHECK		4
CHECK_CLOSE_VAR		5
CHECK_EMPTY_FOLDER		5
CHECK_EMPTY_STR		5
CHECK_EQUAL_STR		5
CHECK_EQUAL_VAR		5
CHECK_EQUAL_WAVES		6
CHECK_NEQ_STR		6
CHECK_NEQ_VAR		6
CHECK_NULL_STR		6
CHECK_SMALL_VAR		7
CHECK_WAVE		7
FAIL		7
REQUIRE		7
REQUIRE_CLOSE_VAR		7
REQUIRE_EMPTY_FOLDER		7
REQUIRE_EMPTY_STR		7
REQUIRE_EQUAL_STR		7
REQUIRE_EQUAL_VAR		7
REQUIRE_EQUAL_WAVES		7
REQUIRE_NEQ_STR		7
REQUIRE_NEQ_VAR		7
REQUIRE_NULL_STR		8
REQUIRE_SMALL_VAR		8
REQUIRE_WAVE		8
WARN		8
WARN_CLOSE_VAR		8
WARN_EMPTY_FOLDER		8
WARN_EMPTY_STR		8
WARN_EQUAL_STR		8
WARN_EQUAL_VAR		8
WARN_EQUAL_WAVES		8
WARN_NEQ_STR		8
WARN_NEQ_VAR		8
WARN_NULL_STR		8
WARN_SMALL_VAR		8
WARN_WAVE		8
U		
UNSIGNED_WAVE		
Wave existence flags		10
W		
WARN		
Test Assertions		8
WARN_CLOSE_VAR		
Test Assertions		8
WARN_EMPTY_STR		
Test Assertions		8
WARN_EQUAL_STR		
Test Assertions		8
WARN_EQUAL_VAR		
Test Assertions		8
WARN_EQUAL_WAVES		
Test Assertions		8
WARN_NEQ_STR		
Test Assertions		8
WARN_NEQ_VAR		
Test Assertions		8
WARN_NULL_STR		
Test Assertions		8
WARN_SMALL_VAR		
Test Assertions		8
WARN_WAVE		
Test Assertions		8
WAVE_DATA		
Wave equality flags		11
WAVE_DATA_TYPE		
Wave equality flags		11
WAVE_LOCK_STATE		
Wave equality flags		11
WAVE_NOTE		
Wave equality flags		11
WAVE_SCALING		
Wave equality flags		11
DATA_FULL_SCALE		11
DATA_UNITS		11
DIMENSION_LABELS		11
DIMENSION_SIZES		11
DIMENSION_UNITS		11
WAVE_DATA		11
WAVE_DATA_TYPE		11
WAVE_LOCK_STATE		11
WAVE_NOTE		11
WAVE_SCALING		11
Wave existence flags		10
COMPLEX_WAVE		10
DOUBLE_WAVE		10
FLOAT_WAVE		10
INT16_WAVE		10
INT32_WAVE		10
INT8_WAVE		10
NUMERIC_WAVE		10
TEXT_WAVE		10
UNSIGNED_WAVE		10